

# JVH.4301F | 3/4" Thermostatic Mixer Valve - 3 Output Page 1 of 2



#### SPECIFICATIONS:

- Turn bottom knob to control temperature.
- Turn top knob to control water flow.
- Thermostatic Valve Flow Rate 22 LPM @ 3 BAR
- Extension Available JVH.4101E\*\*



### **Technical Diagram**





## JVH.4301F | 3/4" Thermostatic Mixer Valve - 3 Output Page 2 of 2

## THREE OUPTUT NO SHARED PORT OPERATION

Diverter Cartridge # - 15100 (Included)

Total 6 Positions as defined below, with **only** 1 port active at one time.

- Position 0 Off No Water Flow
- Position 1 Output B Activated
- Position 2 Off No Water Flow
- Position 3 Output A Activated
- Position 4 Off No Water Flow
- Position 5 Output C Activated

### **THREE OUPTUT - SHARED PORT OPERATION**

Diverter Cartridge # - 15200 (Not Included)

Total 6 Positions as defined below, with 2 ports active at one time.

- Position 0 Off No Water Flow
- Position 1 Output B Activated
- Position 2 Output B+A Activated
- Position 3 Output A Activated
- Position 4 Output C+A Activated
- Position 5 Output C Activated



### Water Diversion Diagram



Diverter Position = 1

Diverter Position = 2

Diverter Position = 3

Diverter Position = off